

(19)



Euro

European Patent Office

Office européen des brevets




(11) Publication number:

**0 675 455 A2**

(12)

**EUROPEAN PATENT APPLICATION**(21) Application number: **95104118.5**(51) Int. Cl.<sup>6</sup>: **G06K 7/01, G06K 19/02**(22) Date of filing: **21.03.95**(30) Priority: **31.03.94 US 220843**(43) Date of publication of application:  
**04.10.95 Bulletin 95/40**(84) Designated Contracting States:  
**DE FR GB IT**(71) Applicant: **THOMSON CONSUMER  
ELECTRONICS, INC.  
10330 North Meridian St.  
Indianapolis, IN 46206 (US)**(72) Inventor: **Ramspacher, Robert James  
13047 Lansdowne Drive  
Fishers / IN (US)  
Inventor: Freeman, Thomas Edward  
321 Deville Place  
New Whiteland / IN (US)**(74) Representative: **Wördemann, Hermes,  
Dipl.-Ing.  
Deutsche Thomson-Brandt GmbH,  
Patent Dept.,  
Göttinger Chaussee 76  
D-30453 Hannover (DE)**(54) **Mechanism for retaining an electronically readable card in an electronic device.**

(57) A device for retaining an electronically readable card (16) in an electronic device includes a substantially V-shaped resilient retainer (15) dimensioned to engage a portion of the card (16) while the rest of the card remains exposed for electronic reading purposes. The resilient retainer (15) is held in the electronic device by a clip (13) having a first detent member (14). The retainer includes a second detent member (17) which engages the first detent member (19) as the retainer enters the slit during insertion of the card into the electronic device. The thicknesses of the retainer and the card and the width of the slit are selected so that the resilient retainer is firmly held in the electronic device.

**EP 0 675 455 A2**

This invention relates generally to pay-to-view television and particularly to a mechanism for retaining an electronically readable card in a pay to view television receiver.

### Background

In pay-to-view television a so-called "smart card" is inserted into the television receiver prior to viewing the intended program. The insertion of the card accomplishes several functions, one of which is the identification of the user as an authorized user. Another function is the billing of the proper viewer of the selected pay-for-view program. Problems can arise with such cards because they can unintentionally fall out, or be removed by children or other unintended person, and as a consequence the cards often get lost. There is a need for a mechanism for retaining the smart card in the television receiver in a snug fashion which enables it to be accurately read and which prevents it from accidentally falling out or being inadvertently removed by children. The invention fulfills these needs.

### Summary

A mechanism for retaining an electronically readable card in an electronic device includes a bezel having an opening for inserting and holding the card in the electronic device. A resilient clip, which is dimensioned and configured to snap into the opening, includes a slit and has a detent member. A substantially V-shaped resilient retainer is dimensioned to engage one portion of the card while the remainder of the card remains exposed for electronic reading purposes. The resilient retainer includes a second detent member which engages the first detent member of the projection as the retainer enters the slit during insertion of the card into the electronic device, to firmly hold the resilient retainer in the electronic device.

### Brief Description of the Drawings

FIGURE 1 is a cross section of a preferred embodiment.

FIGURE 2 shows an embodiment of a resilient V-shaped retainer in detail.

FIGURE 3 is another embodiment of the resilient V-shaped retainer.

FIGURE 4 is a cross section of another preferred embodiment, shown partially broken away.

### Detailed Description

In FIGURE 1 a bezel 11 includes an opening 12 and is permanently affixed to a television re-

ceiver 10, shown broken away, which can be used to view pay-for-view television programs. A resilient clip 13 is configured to conform to the shape of the opening 12 and is dimensioned to snap-fit into the opening. The clip is held in the bezel 11 by lips 13a. Resilient clip 13 includes a longitudinal slit 14. The slit 14 is dimensioned in length and width to snugly receive a V-shaped resilient retainer 15 which is used to hold the "smart card" 16 in the television receiver. The retainer 15 firmly engages the full length of the card 16 (not shown). The cross-sectional width of the resilient retainer 15 is selected to engage only that portion of the thickness of the card 16 required to ensure that the card cannot accidentally fall from the receiver, or be inadvertently removed by a small child or some other person who is not intended to remove the card. A substantial portion of the width of the smart card 16 remains uncovered by resilient retainer 15 and extends into the receiver to be read by an electronic mechanism of known type to identify the receiver, bill the appropriate customer and what ever other functions are programmed onto the card.

As shown in FIGURE 2, resilient retainer 15 includes apertures 18 on both of the sides, forming the "V" shape. Resilient clip 13 includes projections 17 (Figure 1) which engage the apertures 18 to firmly hold the resilient retainer 15 and smart card 16 in the desired position. The thicknesses of retainer 15, card 16 and the width of slit 14 are selected so that clip 13 abuttingly biases the retainer 15 against the card 16 to firmly hold the card in the holder 11. A V-shaped spring 19 can be embedded in or arranged in the resilient retainer 15 to increase the resilience of the retainer.

In FIGURE 3 the detent member for the resilient V-shaped retainer is composed of ribs 19 extending along the length of both sides of the retainer 15. The ribs 19 engage the edge 20 of resilient clip 13 to hold the resilient retainer 15 in the TV receiver. In this embodiment, the ribs 19 and edge 20 replace the projections 17 and apertures 18.

The FIGURE 4 embodiment is similar to the FIGURE 1 embodiment. However, resilient clip 13 includes apertures 18a (shown as blind holes) and resilient retainer 15a includes projections 17a.

### Claims

1. A mechanism for retaining an electronically readable card (116) in an electronic device having a holder including an opening (12) for inserting and holding said card in said electronic device, said mechanism characterized by:

a resilient clip (13) dimensioned and con-

figured to snap into said opening (12) and including a slit, said clip (13) also includes a first detent member (14,18a);

a substantially V-shaped resilient retainer (15) dimensioned to engage one portion of said card (16) while another portion of said card (16) remains exposed for electronic reading purposes, said retainer (15) including a second detent member (17,17a) for engaging said first detent member (14) when said retainer enters said slit during insertion of said card into said electronic device (13).

2. The mechanism of claim 1 characterized in that said first detent member includes at least one projection (14) extending into said slit, and said second detent member includes at least one aperture (17) for receiving said projection.
3. The mechanism of claim 1 characterized in that said first detent member includes at least one aperture (18a), and said second detent member includes at least one projection (17a) for being received in said aperture.
4. The mechanism of claim 1 characterized in that said first detent member includes an edge of said resilient clip (13) and said second detent member includes at least one rib (19) extending along a selected length of said resilient retainer.
5. The mechanism of claim 2 characterized in that the thicknesses of said resilient retainer and said card and the width of said slit are selected whereby said clip biases said retainer against said card to firmly engage said retainer against said card.
6. The mechanism of claim 3 characterized in that the thicknesses of said resilient retainer and said card and the width of said slit are selected whereby said clip biases said retainer against said card to firmly engage said retainer against said card.
7. The mechanism of claim 4 characterized in that the thicknesses of said resilient retainer and said card and the width of said slit are selected whereby said clip biases said retainer against said card to firmly engage said retainer against said card.
8. The mechanism of claim 1 characterized in that a spring for biasing said resilient retainer open.
9. The mechanism of claim 2 characterized in that a spring for biasing said resilient retainer open.
10. The mechanism of claim 3 characterized in that a spring for biasing said resilient retainer open.




FIG 1




FIG 2




FIG 3




FIG 4

**THIS PAGE BLANK (USPTO)**

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 0 675 455 A3**

(12)

**EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
05.04.2000 Bulletin 2000/14

(51) Int. Cl.<sup>7</sup>: **G06K 7/01**, G06K 19/02,  
G06K 7/00

(43) Date of publication A2:  
04.10.1995 Bulletin 1995/40

(21) Application number: **95104118.5**

(22) Date of filing: **21.03.1995**

(84) Designated Contracting States:  
**DE FR GB IT**

(30) Priority: **31.03.1994 US 220843**

(71) Applicant:  
**THOMSON CONSUMER ELECTRONICS, INC.**  
Indianapolis, IN 46206 (US)

(72) Inventors:  
• **Ramspacher, Robert James**  
Fishers / IN (US)


• **Freeman, Thomas Edward**  
New Whiteland / IN (US)

(74) Representative:  
**Wördemann, Hermes, Dipl.-Ing.**  
**Deutsche Thomson-Brandt GmbH,**  
Licensing & Intellectual Property,  
Karl-Wiechert-Allee 74  
30625 Hannover (DE)

**(54) Mechanism for retaining an electronically readable card in an electronic device**

(57) A device for retaining an electronically readable card (16) in an electronic device includes a substantially V-shaped resilient retainer (15) dimensioned to engage a portion of the card (16) while the rest of the card remains exposed for electronic reading purposes. The resilient retainer (15) is held in the electronic device by a clip (13) having a first detent member (14). The

retainer includes a second detent member (17) which engages the first detent member (19) as the retainer enters the slit during insertion of the card into the electronic device. The thicknesses of the retainer and the card and the width of the slit are selected so that the resilient retainer is firmly held in the electronic device.



**FIG 1**

**EP 0 675 455 A3**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 95 10 4118

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cls.)
A	US 5 276 317 A (OZOUF RENE ET AL) 4 January 1994 (1994-01-04) * column 1, line 63 - column 2, line 25 * * column 3, line 32 - line 45 * * column 3, line 58 - column 4, line 10 * * figures 4-6 *	1,3,4	G06K7/01 G06K19/02 G06K7/00
A	US 4 814 593 A (REICHARDT MANFRED ET AL) 21 March 1989 (1989-03-21) * column 2, line 1 - line 30 * * column 6, line 15 - column 7, line 25 * * claims 2-5; figures 7,8 *	1	
A	US 4 192 422 A (KOTYUK BERNARD) 11 March 1980 (1980-03-11) * column 3, line 3 - line 23 * * column 7, line 39 - column 8, line 3 * * figures 17,18 *	1,2	
			TECHNICAL FIELDS SEARCHED (Int.Cls.)
			G06K H04N A45C
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>10 February 2000</b>	Examiner <b>Bhalodia, A</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone  Y : particularly relevant if combined with another document of the same category  A : technological background  O : non-written disclosure  P : intermediate document</p> <p>T : theory or principle underlying the invention  E : earlier patent document, but published on, or after the filing date  D : document cited in the application  L : document cited for other reasons  &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.92 (P04001)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 95 10 4118

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

10-02-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5276317 A	04-01-1994	FR 2665556 A	07-02-1992
		AT 126420 T	15-09-1995
		AU 646874 B	10-03-1994
		AU 8130691 A	06-02-1992
		DE 69112154 D	21-09-1995
		DE 69112154 T	04-01-1996
		DK 469503 T	27-11-1995
		EP 0469503 A	05-02-1992
		ES 2076427 T	01-11-1995
		GR 3017551 T	31-12-1995
		JP 6020115 A	28-01-1994
US 4814593 A	21-03-1989	DE 3625306 A	28-01-1988
		EP 0254316 A	27-01-1988
		JP 63106091 A	11-05-1988
US 4192422 A	11-03-1980	US 4120400 A	17-10-1978

**THIS PAGE BLANK (USPTO)**